

# Yeastar TE Series E1/T1/PRI VoIP Gateway



Yeastar TE100/200 offers SMBs cost effective additions to legacy telephone systems to bring the true benefits of VoIP. TE100/200 is a single or dual port VoIP E1/T1/J1 gateway (VoIP to E1/T1/J1, and E1/T1/J1 to VoIP) that supports up to 30 or 60 concurrent calls. It's designed to bridge the gap between E1/T1/J1 and VoIP networks. Integrating TE100/200 into an existing network will allow inexpensive communication via SIP trunking. Also, it could connect VoIP systems with E1/T1/J1 service from legacy carriers.

## Features & Benefits

- Up to 60 simultaneous VoIP to ISDN PRI calls
- Software configurable E1/T1/J1 ports and programmable TE/NT Modes
- Flexible and cost-effective call routing to reduce communication costs
- Simple installation and management with easy-to-navigate Web GUI
- Connect existing ISDN PBX to VoIP and retain the dialing habits
- Bring E1/T1 trunks to a VoIP-only system to route calls to ISDN
- Connect multiple PABX at different sites over IP networks
- Compatible with various ISDN PBX, IP-PBX, and softswitch



Yeastar Information Technology Co., Ltd.

Tel: 86-592-5503309

Email: [sales@yeastar.com](mailto:sales@yeastar.com)

Web: [www.yeastar.com](http://www.yeastar.com)

## Physical Interfaces

- E1/T1/J1 port: 1 or 2
- Dual Base-T connectors
- TE100: 10/100 Mbps
- TE200: 10/100/1000 Mbps
- USB port:1

## Voice Processing

- Protocol: SIP(RFC3261)
- DTMF: RFC2833, SIP Info, In-band.
- Codec: G711a, G711u, G.722, G.726, G.729a, GSM, Speex, ADPCM
- Transport: UDP, TCP, TLS, SRTP
- Echo Cancellation: ITU-T G.168 LEC

## Telephony

- Blocklist
- Call detail records
- Call duration limitation
- Caller ID
- Caller ID prefix
- Call routing rules
- SIP trunk support
- SIP peer mode
- SIP Registrar for IP phones
- T.38 fax
- Trunk group

## Signalling

- PRI switch types: Euro ISDN, nation, Q.SIG
- CAS: MFC R2 (Argentina, Brazil, China, Czech Republic, Colombia, Ecuador, Indonesia, ITU, Mexico, Philippines, Venezuela)
- SS7: ITU, ANSI, China

## Internet

- DDNS
- IP Blocklist
- NAT Traversal
- QoS/ToS
- PPPoE
- Static Route

## System

- Backup and restore
- Custom prompts
- E1/T1/J1 diagnostics
- Firmware upgrade by HTTP/TFTP
- Packet Capture Tool
- System logs
- Security: Firewall, TLS, SRTP, HTTPS
- Web based configuration

## Applications

- Connect legacy PBX to VoIP services
- Connect IP-PBX to ISDN trunkings
- ISDN connectivity for Contact Center
- Connect legacy PBX to IP-PBX at the branch office
- Interconnect multiple PABX to realize free inter-office calls

## Physical

- Dimensions: 213x160x44 mm
- Power Supply: AC 100-240V (12V 2A)
- Operation Range: 0°C to 40°C, 32°F to 104°F
- Storage Range: -20°C to 65°C, -4°F to 149°F
- Humidity: 10-90% non-condensing